

12/23/99 JC688 U.S. PTO

12-27-99

Attorney's Docket No. 99-0740  
Client's Docket No. FLO102

JC678 U.S. PTO  
09/470756  
12/23/99

**PATENT Utility APPLICATION COVER SHEET**

BOX PATENT APPLICATION  
HONORABLE ASSISTANT COMMISSIONER FOR PATENTS  
Washington, D. C. 20231

Sir:

Transmitted herewith for filing is the utility patent application  
of:

INVENTOR: GLENNAH D HART

FOR: CARDIAC TELEMETRY PROTECTIVE POUCH

**Enclosed are:**


- ☒ Postcard for receipt stamp and return.
- ☒ Applicant's Check for **\$385.00**, covering fees calculated below.
- ☒ Specification with Claims, Abstract, & Declaration & Power of Attorney
- ☒ A verified statement to establish small entity status under 37C.F.R § 1.9 and 37 C.F.R. § 1.27.
- ☒ 2 sheets of drawing.  
Cover Sheet & Assignment to: \_\_\_\_\_  
Information Disclosure Statement.

**The filing fee has been calculated as shown below:**

	(Col. 1) No. Filed	(Col. 2) No. Extra		SMALL ENTITY RATE	FEE
FOR:					
BASIC FEE				\$380	\$380
TOTAL CLAIMS	8	-20=	0	x09	0
INDEPENDENT CLAIMS	2	- 3=	0	x39	0
MULTIPLE DEPENDENT CLAIMS PRESENTED				+125	
<b>TOTAL</b>					<b>\$380</b>

DEPOSIT ACCOUNT AUTHORIZATION

The Commissioner is hereby authorized to charge any fees, which are not otherwise submitted and which may be required under 37 CFR 1.17 during the entire pendency of this application, to the Deposit Account # **11-0020**.

  
\_\_\_\_\_  
IVAR M. KAARDAL, Reg. No. 29,812  
KAARDAL & ASSOCIATES, PC  
3500 South First Ave. Circle-Suite 250  
SIOUX FALLS, SD 57105-5807  
(605) 336-9446 FAX (605) 336-1931  
e-mail: patent@kaardal.com

December 23, 1999

Date

Attorney's Docket No. 99-0740  
Client's Docket No. FLO102

**In the United States Patent and Trademark Office**

In re Application of:  
GLENNAH D HART

Filed: **UTILITY PATENT APPLICATION**

For: **CARDIAC TELEMETRY PROTECTIVE POUCH**

Assistant Commissioner for Patents and Trademarks  
Washington, D.C. 20231

Date of Deposit: December 23, 1999

I hereby certify that the attached U.S. Patent Application, informal drawings, transmittal letter, priority document, and/or Preliminary Amendment are being deposited with the United States Postal Service under Express Mail service **#EL 248492052 US** on the date indicated above and is addressed to the Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

Barbara Roos

December 23, 1999  
Date

BARBARA ROOS  
KAARDAL & ASSOCIATES, PC  
3500 South First Ave. Circle-Suite 250  
SIOUX FALLS, SD 57105-5807  
(605) 336-9446 FAX (605) 336-1931  
e-mail patent@kaardal.com

Attorney's Docket No. K&A 99-0740  
Client's Docket No. FLO102

**APPLICATION**

**FOR UNITED STATES LETTERS PATENT**

----

**SPECIFICATION**

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT I, **GLENNAH D. HART**, a citizen of  
UNITED STATES OF AMERICA, have invented a new and useful  
**CARDIAC TELEMETRY PROTECTIVE POUCH** of which the  
following is a specification:

# CARDIAC TELEMETRY PROTECTIVE POUCH

5

## BACKGROUND OF THE INVENTION

### Field of the Invention

10

The present invention relates to protective coverings for electronic devices and more particularly pertains to a new cardiac telemetry protective pouch for providing a water resilient protective pouch for containing the telemetry electronics employed for monitoring and transmitting cardiac status information about a patient.

15

### Description of the Prior Art

20

The use of protective coverings for electronic devices is known in the prior art. More specifically, protective coverings for electronic devices heretofore devised and utilized are known to consist basically of familiar, expected and obvious structural configurations, notwithstanding the myriad of designs encompassed by the crowded prior art which have been developed for the fulfillment of countless objectives and requirements.

25

Known prior art includes U.S. Patent No. 5,063,919; U.S. Patent No. 5,342,286; U.S. Patent No. Des. 360,414; U.S. Patent

No. 4,911,151; U.S. Patent No. 4,043,326; and U.S. Patent No. 2,244,871.

While these devices fulfill their respective, particular  
5 objectives and requirements, the aforementioned patents do not  
disclose a new cardiac telemetry protective pouch. The inventive  
device includes a protective pouch for receiving the telemetry  
device of the cardiac telemetry monitoring apparatus. The  
protective pouch comprises a pair of side panels each having a  
10 perimeter. A portion of the perimeter of a first one of the side  
panels is releasably coupled to a corresponding portion of the  
perimeter of a second one of the side panels to form a closable  
opening on the pouch. A remainder portion of the perimeter of the  
first side panel is inseparably coupled to the perimeter of the  
15 second side panel to define an interior and form a water tight seal  
between the side panels at the remainder portion. An interlocking  
closure is for releasably joining the side panels at the closable  
opening. The interlocking closure comprises a first interlocking  
structure on the first side panel and a second interlocking structure  
20 on the second side panel. The first interlocking structure of the  
first side panel and second interlocking structure of the second  
panel each have at least one gap therein at alignable locations of  
the closable opening such that a hole is formed between the first  
and second side panels when the first and second interlocking  
25 structures of the side panels are interlocked together for permitting  
passage of a lead wire through the interlocking closure when the  
first interlocking structure are interlocked with the second  
interlocking structure in snug relationship with the lead wire.

30 In these respects, the cardiac telemetry protective pouch  
according to the present invention substantially departs from the

conventional concepts and designs of the prior art, and in so doing provides an apparatus primarily developed for the purpose of providing a water resilient protective pouch for containing the telemetry electronics employed for monitoring and transmitting cardiac status information about a patient.

## SUMMARY OF THE INVENTION

In view of the foregoing disadvantages inherent in the known types of protective coverings for electronic devices now present in the prior art, the present invention provides a new cardiac telemetry protective pouch construction wherein the same can be utilized for providing a water resilient protective pouch for containing the telemetry electronics employed for monitoring and transmitting cardiac status information about a patient.

The general purpose of the present invention, which will be described subsequently in greater detail, is to provide a new cardiac telemetry protective pouch apparatus and method which has many of the advantages of the protective coverings for electronic devices mentioned heretofore and many novel features that result in a new cardiac telemetry protective pouch which is not anticipated, rendered obvious, suggested, or even implied by any of the prior art protective coverings for electronic devices, either alone or in any combination thereof.

To attain this, the present invention generally comprises a protective pouch for receiving the telemetry device of the cardiac telemetry monitoring apparatus. The protective pouch comprises a pair of side panels each having a perimeter. A portion of the perimeter of a first one of the side panels is releasably coupled to a corresponding portion of the perimeter of a second one of the side

panels to form a closable opening on the pouch. A remainder portion of the perimeter of the first side panel is inseparably coupled to the perimeter of the second side panel to define an interior and form a water tight seal between the side panels at the remainder portion. An interlocking closure is for releasably joining the side panels at the closable opening. The interlocking closure comprises a first interlocking structure on the first side panel and a second interlocking structure on the second side panel. The first interlocking structure of the first side panel and second interlocking structure of the second panel each have at least one gap therein at alignable locations of the closable opening such that a hole is formed between the first and second side panels when the first and second interlocking structures of the side panels are interlocked together for permitting passage of a lead wire through the interlocking closure when the first interlocking structure are interlocked with the second interlocking structure in snug relationship with the lead wire.

There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the invention that will be described hereinafter and which will form the subject matter of the claims appended hereto.

In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable

of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting.

5

As such, those skilled in the art will appreciate that the conception, upon which this disclosure is based, may readily be utilized as a basis for the designing of other structures, methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

Further, the purpose of the foregoing abstract is to enable the U.S. Patent and Trademark Office and the public generally, and especially the scientists, engineers and practitioners in the art who are not familiar with patent or legal terms or phraseology, to determine quickly from a cursory inspection the nature and essence of the technical disclosure of the application. The abstract is neither intended to define the invention of the application, which is measured by the claims, nor is it intended to be limiting as to the scope of the invention in any way.

It is therefore an object of the present invention to provide a new cardiac telemetry protective pouch apparatus and method which has many of the advantages of the protective coverings for electronic devices mentioned heretofore and many novel features that result in a new cardiac telemetry protective pouch which is not anticipated, rendered obvious, suggested, or even implied by any of the prior art protective coverings for electronic devices, either alone or in any combination thereof.



It is another object of the present invention to provide a new cardiac telemetry protective pouch which may be easily and efficiently manufactured and marketed.

5

It is a further object of the present invention to provide a new cardiac telemetry protective pouch which is of a durable and reliable construction.

10

An even further object of the present invention is to provide a new cardiac telemetry protective pouch which is susceptible of a low cost of manufacture with regard to both materials and labor, and which accordingly is then susceptible of low prices of sale to the consuming public, thereby making such cardiac telemetry protective pouch economically available to the buying public.

15

Still yet another object of the present invention is to provide a new cardiac telemetry protective pouch which provides in the apparatuses and methods of the prior art some of the advantages thereof, while simultaneously overcoming some of the disadvantages normally associated therewith.

20

Still another object of the present invention is to provide a new cardiac telemetry protective pouch for providing a water resilient protective pouch for containing the telemetry electronics employed for monitoring and transmitting cardiac status information about a patient.

25

Yet another object of the present invention is to provide a new cardiac telemetry protective pouch which includes a protective pouch for receiving the telemetry device of the cardiac telemetry monitoring apparatus. The protective pouch comprises a pair of

30

side panels each having a perimeter. A portion of the perimeter of a first one of the side panels is releasably coupled to a corresponding portion of the perimeter of a second one of the side panels to form a closable opening on the pouch. A remainder  
5 portion of the perimeter of the first side panel is inseparably coupled to the perimeter of the second side panel to define an interior and form a water tight seal between the side panels at the remainder portion. An interlocking closure is for releasably joining the side panels at the closable opening. The interlocking closure  
10 comprises a first interlocking structure on the first side panel and a second interlocking structure on the second side panel. The first interlocking structure of the first side panel and second interlocking structure of the second panel each have at least one gap therein at alignable locations of the closable opening such that  
15 a hole is formed between the first and second side panels when the first and second interlocking structures of the side panels are interlocked together for permitting passage of a lead wire through the interlocking closure when the first interlocking structure are interlocked with the second interlocking structure in snug  
20 relationship with the lead wire.

Still yet another object of the present invention is to provide a new cardiac telemetry protective pouch that provides a substantially watertight pouch in which sensitive telemetry  
25 electronics may be held during patient activities such, for example, during patient showers.

Even still another object of the present invention is to provide a new cardiac telemetry protective pouch that provides a  
30 pouch that shields the more water sensitive portion of the telemetry equipment while leaving the less water sensitive portions exposed.

These together with other objects of the invention, along with the various features of novelty which characterize the invention, are pointed out with particularity in the claims annexed to and  
5 forming a part of this disclosure. For a better understanding of the invention, its operating advantages and the specific objects attained by its uses, reference should be made to the accompanying drawings and descriptive matter in which there are illustrated preferred embodiments of the invention.

## 10 **BRIEF DESCRIPTION OF THE DRAWINGS**

The invention will be better understood and objects other than those set forth above will become apparent when consideration is  
15 given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

Figure 1 is a perspective view of a new cardiac telemetry protective pouch according to the present invention.

20 Figure 2 is a top plan view of the present invention.

Figure 3 is an enlarged perspective view of the interlocking closure of the present invention.

25 Figure 4 is a top view of the lead wire covers of the present invention.

## 30 **DESCRIPTION OF THE PREFERRED EMBODIMENT**

With reference now to the drawings, and in particular to Figures 1 through 4 thereof, a new cardiac telemetry protective pouch embodying the principles and concepts of the present

invention and generally designated by the reference numeral 10 will be described.

As best illustrated in Figures 1 through 4, the cardiac  
5 telemetry protective pouch 10 generally comprises a cardiac  
telemetry monitoring apparatus for monitoring and transmitting  
information about the cardiac status of a patient. The cardiac  
telemetry monitoring apparatus comprises a telemetry device 11, a  
housing, and a battery compartment in the housing. A plurality of  
10 lead wires 12 are removably connected to the telemetry device,  
wherein the plurality of lead wires comprises five lead wires. A  
plurality of electrodes 13 each connected to one of the plurality of  
lead wires.

15 A protective pouch 14 for receiving the telemetry device of  
the cardiac telemetry monitoring apparatus. The protective pouch  
comprises a pair of side panels each having a perimeter. A portion  
of the perimeter of a first one of the side panels 15 is releasably  
coupled to a corresponding portion of the perimeter of a second one  
20 of the side panels 16 to form a closable opening on the pouch. A  
remainder portion of the perimeter of the first side panel is  
inseparably coupled to the perimeter of the second side panel to  
define an interior 17 and form a water tight seal between the side  
panels at the remainder portion.

25

An interlocking closure 18 is for releasably joining the side  
panels at the closable opening. The interlocking closure comprises  
a first interlocking structure 19 on the first side panel and a second  
interlocking structure 20 on the second side panel. The first  
30 interlocking structure comprises a pair of protruding lips 22  
extending in a spaced parallel relationship along the portion of the

first side panel forming the closable opening. The second interlocking structure comprises at least one protruding lip 23 extending along the portion of the second side panel forming the closable opening and is releasably insertable between and

5 interlockable with the pair of protruding lips of the first side panel. The first interlocking structure of the first side panel and second interlocking structure of the second panel each have at least one gap therein at alignable locations of the closable opening such that a hole is formed between the first and second side panels when the

10 first and second interlocking structures of the side panels are interlocked together for permitting passage of a lead wire through the interlocking closure when the first interlocking structures are interlocked with the second interlocking structures in snug relationship with the lead wire.

15 A plurality of gaps 24 are formed in the first and second interlocking structures and adjacent gaps are separated by segments of the first and second interlocking structures. The interlocking closure comprises at least five holes in the interlocking closure for

20 permitting at least five leads to extend out of the interior. A lip segment 26 on each of the first and second interlocking structures extends between adjacent gaps in the protruding lips of the first and second interlocking structures. One of the lip segments of the first interlocking structure is interlockable with one of the lip segments

25 of the second interlocking structure.

A grommet 27 extends through the first and second side panels. The grommet is located on the pouch at a location spaced from the closable opening such that when the pouch is suspended

30 from the grommet, the pouch hangs in an inverted position with the

closable opening directed downwardly to shed water away from the closable opening. The grommet comprises an aperture 28 therethrough. The grommet is substantially circular. A tether strap 29 is for supporting the pouch in a shower stall. The tether strap 5 comprises an endless loop extending through the aperture of the grommet.

In an embodiment a plurality of lead wire covers 30 may be provided which encompass the lead wires therein and protect the 10 lead wires from contact with water. The lead wire covers are formed such that the lead wire covers fit in the gaps formed in the first and second interlocking structures such that a water resistant seal is formed between the lead wire covers and the interlocking structures when the interlocking structures are sealed.

15 In use, a user would place the telemetry apparatus within the pouch and place the lead wire covers over the lead wires of the telemetry unit. The closable end of the pouch would then be sealed with the lead wires protruding outwardly from the pouch. The lead 20 wires could then be placed upon a patient and the tether strap slung over the shoulder to aid in the carrying of the telemetry unit.

As to a further discussion of the manner of usage and operation of the present invention, the same should be apparent 25 from the above description. Accordingly, no further discussion relating to the manner of usage and operation will be provided.

With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of the 30 invention, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed

readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by the present invention.

5

Therefore, the foregoing is considered as illustrative only of the principles of the invention. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the invention.

10

## CLAIMS

I claim:

1. A cardiac telemetry protective system for protective carrying of monitoring and transmitting cardiac information of a patient, the cardiac telemetry protective system comprising:

a protective pouch for receiving the telemetry device of the cardiac telemetry monitoring apparatus, the protective pouch comprising:

a pair of side panels each having a perimeter, a portion of the perimeter of a first one of the side panels being releasably coupled to a corresponding portion of the perimeter of a second one of the side panels to form a closable opening on the pouch, a remainder portion of the perimeter of the first side panel being inseparably coupled to the perimeter of the second side panel to define an interior and form a water tight seal between the side panels at the remainder portion; and

an interlocking closure for releasably joining the side panels at the closable opening, the interlocking closure comprising a first interlocking structure on the first side panel and a second interlocking structure on the second side panel, wherein the first interlocking structure of the first side panel and second interlocking structure of the second panel each have at least one gap therein at alignable locations of the closable opening such that a hole is formed between the first and second side panels when the first and second



interlocking structures of the side panels are interlocked together for permitting passage of a lead wire through the interlocking closure when the first interlocking structures are interlocked with the second interlocking structures in snug relationship with the lead wire.

2. The cardiac telemetry protective system as set forth in claim 1 wherein the first interlocking structure comprising a pair of protruding lips extending in a spaced parallel relationship along the portion of the first side panel forming the closable opening, the second interlocking structure comprising at least one protruding lip extending along the portion of the second side panel forming the closable opening and being releasably insertable between and interlockable with the pair of protruding lips of the first side panel.

3. The cardiac telemetry protective system as set forth in claim 1 wherein a plurality of gaps are formed in the first and second interlocking structures and adjacent gaps are separated by segments of the first and second interlocking structures.

4. The cardiac telemetry protective system as set forth in claim 3 wherein the interlocking closure having at least five holes in the interlocking closure for permitting at least five leads to extend out of the interior.

5. The cardiac telemetry protective system as set forth in claim 1 wherein a lip segment on each of the first and second interlocking structures extending between adjacent gaps in the protruding lips of the first and second interlocking structures, one of the lip segments of the first interlocking structure being

interlockable with one of the lip segments of the second interlocking structure;

6. The cardiac telemetry protective system as set forth in claim 1 further comprises a grommet extending through the first and second side panels, the grommet being located on the pouch at a location spaced from the closable opening such that when the pouch is suspended from the grommet, the pouch hangs in an inverted position with the closable opening directed downwardly to shed water away from the closable opening, the grommet having an aperture therethrough, the grommet being substantially circular.

7. The cardiac telemetry protective system as set forth in claim 6 further comprises a tether strap for supporting the pouch in a shower stall, the tether strap comprising an endless loop extending through the aperture of the grommet.

8. A cardiac telemetry protective system for protective carrying of monitoring and transmitting cardiac information of a patient, the cardiac telemetry protective system comprising:

a cardiac telemetry monitoring apparatus for monitoring and transmitting information about the cardiac status of a patient, the cardiac telemetry monitoring apparatus comprising:  
a telemetry device, a housing, a battery compartment in the housing;  
a plurality of lead wires removably connected to the telemetry device, wherein the plurality of lead wires comprises five lead wires;

a plurality of electrodes, each of the electrodes being connected to one of the plurality of lead wires;

a protective pouch for receiving the telemetry device of the cardiac telemetry monitoring apparatus, the protective pouch comprising:

a pair of side panels each having a perimeter, a portion of the perimeter of a first one of the side panels being releasably coupled to a corresponding portion of the perimeter of a second one of the side panels to form a closable opening on the pouch, a remainder portion of the perimeter of the first side panel being inseparably coupled to the perimeter of the second side panel to define an interior and form a water tight seal between the side panels at the remainder portion;

an interlocking closure for releasably joining the side panels at the closable opening, the interlocking closure comprising a first interlocking structure on the first side panel and a second interlocking structure on the second side panel, the first interlocking structure comprising a pair of protruding lips extending in a spaced parallel relationship along the portion of the first side panel forming the closable opening, the second interlocking structure comprising at least one protruding lip extending along the portion of the second side panel forming the closable opening and being releasably insertable between and interlockable with the pair of protruding lips of the first side panel, wherein the first interlocking structure of the first side panel and second interlocking structure of the second panel each have at least one gap therein at alignable locations of the closable opening such that a hole is formed between the



first and second side panels when the first and second interlocking structures of the side panels are interlocked together for permitting passage of a lead wire through the interlocking closure when the first interlocking structures are interlocked with the second interlocking structures in snug relationship with the lead wire, wherein a plurality of gaps are formed in the first and second interlocking structures and adjacent gaps are separated by segments of the first and second interlocking structures, the interlocking closure having at least five holes in the interlocking closure for permitting at least five leads to extend out of the interior, a lip segment on each of the first and second interlocking structures extending between adjacent gaps in the protruding lips of the first and second interlocking structures, one of the lip segments of the first interlocking structure being interlockable with one of the lip segments of the second interlocking structure;

a grommet extending through the first and second side panels, the grommet being located on the pouch at a location spaced from the closable opening such that when the pouch is suspended from the grommet, the pouch hangs in an inverted position with the closable opening directed downwardly to shed water away from the closable opening, the grommet having an aperture therethrough, the grommet being substantially circular; and

a tether strap for supporting the pouch in a shower stall, the tether strap comprising an endless loop extending through the aperture of the grommet.

**ABSTRACT OF THE DISCLOSURE**

5           A cardiac telemetry protective pouch for providing a water  
resilient protective pouch for containing the telemetry electronics  
employed for monitoring and transmitting cardiac status  
information about a patient. The cardiac telemetry protective  
pouch includes a protective pouch comprising a pair of side panels  
10 each having a perimeter. A portion of the perimeter of a first one  
of the side panels is releasably coupled to a corresponding portion  
of the perimeter of a second one of the side panels to form a  
closable opening on the pouch. A remainder portion of the  
perimeter of the first side panel is inseparably coupled to the  
15 perimeter of the second side panel to define an interior and form a  
water tight seal between the side panels at the remainder portion.  
An interlocking closure comprises a first interlocking structure on  
the first side panel and a second interlocking structure on the  
second side panel. The first interlocking structure of the first side  
20 panel and second interlocking structure of the second panel each  
have at least one gap therein at alignable locations of the closable  
opening such that a hole is formed between the first and second  
side panels when the first and second interlocking structures of the  
side panels are interlocked together for permitting passage of a lead  
25 wire through the interlocking closure when the first interlocking  
structure are interlocked with the second interlocking structure in  
snug relationship with the lead wire.






FIG. 3




FIG. 4

## DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

### CARDIAC TELEMETRY PROTECTIVE POUCH

the specification of which is attached hereto.

I further state that I do not know and do not believe that the above-named invention has ever been known or used in the United States before my invention thereof, or patented or described in any printed publication in any country before my invention thereof, or in public use or on sale in the United States more than one year prior to this application; that the invention has not been patented or made the subject of any inventor's certificate in any country foreign to the United States on any application filed by me or my legal representatives or assigns more than one (1) year prior to this application; and that no application for patent or inventor's certificate on the invention has been filed by me or my representatives or assigns in any country foreign to the United States, except as identified below.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment if applicable.

I acknowledge the duty to disclose information to the Patent and Trademark Office all information known to me to be material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed



<u>NONE</u>	<u>                    </u>	<u>                    </u>	<u>                    </u>	<u>                    </u>
(Number)	(Country)	(Day/Month/ Year Filed)	(Yes)	(No)

I hereby claim the benefit under 35 U.S.C. Section 119(e) of any United States Provisional application(s) listed below:

<u>NONE</u>	<u>                    </u>
(Application No.)	(Filing Date)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or Section 365 (c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, Section 112. I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

<u>NONE</u>	<u>                    </u>	<u>                    </u>
(Application No.)	(Filing Date)	(Status - patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorneys to prosecute this application and transact all business in the U.S. Patent and Trademark Office connected therewith: Ivar M. Kaardal, Registration Number 29,812.

Send Correspondence to: Kaardal & Associates, PC  
Attn: Ivar M. Kaardal  
3500 South First Ave. Circle - Suite 250  
Sioux Falls, South Dakota 57105-5807  
Telephone (605) 336-9446, FAX (605) 336-1931  
e-mail: patent@kaardal.com

Full Name of Inventor: **GLENNAH D. HART**

Glennah D. Hart  
Inventor's Signature

Date: 12-9-99

Residence: **COLUMBIA, SOUTH CAROLINA**

Citizenship: **UNITED STATES OF AMERICA**

Post Office Address: **P.O. BOX 4565  
COLUMBIA, SC 29240**

Applicant or Patentee: **GLENNAH D. HART**  
Serial or Patent Number:  
Filed or Issued:  
For: **CARDIAC TELEMETRY PROTECTIVE POUCH**

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY  
STATUS (37 CFR 1.9(f) and 1.27(b) - INDEPENDENT INVENTOR**

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled as above and described in:

☒ the specification filed herewith.  
☐ application serial number \_\_\_\_\_, filed \_\_\_\_\_.  
☐ patent no. \_\_\_\_\_, issued \_\_\_\_\_.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

☒ no such person, concern, or organization  
☐ persons, concerns or organizations listed below\*

\*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

FULL NAME: NOT APPLICABLE ☐ INDIVIDUAL  
ADDRESS: NOT APPLICABLE ☐ SMALL BUSINESS CONCERN  
☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF INVENTOR: **GLENNAH D. HART**

Glennah D. Hart  
Inventor's Signature

Date: 12-9-99